



REVISION RECORD			
REV	ECO	DESCRIPTION	DRFT DATE
Δ		Drawing amend	Home 04/17/06*
Δ		增加环保标示	Ye J 10/30/07

Notes

1. pitch: 5.08mm
2. Rated voltage: 300V
3. Rated current: 15A
4. Insulation resistance: 5000MΩ/DC1000V
5. Withstanding voltage: AC2000V/1Min
6. Temp. Range: -40° C~+105° C
7. Undimensioned Tolerances:

Pitch range in mm		Nominal dimension range	
over	under	over	under
10	6	10	6
15	10	15	10
20	15	20	15
25	20	25	20
30	25	30	25
35	30	35	30
40	35	40	35
45	40	45	40
50	45	50	45

ITEM	DESCRIPTION	QTY	MATERIAL	NOTES
1	HT508V Housing	1	PA66	UL94V-0
2	2EDGV Pin heads(1.0X13.7)	XX	Brass	SnCe

  

DETACHED LISTS	
UNIT	UNIT
MM	INCH
0.00 ±	±
0.05 ±	±
0.10 ±	±
0.20 ±	±
0.30 ±	±
0.50 ±	±
1.00 ±	±
1.50 ±	±
2.00 ±	±
3.00 ±	±
4.00 ±	±
5.00 ±	±
6.00 ±	±
8.00 ±	±
10.00 ±	±

  

DATE	DATE	DATE	DATE
08/03/04			

  

NAME	DEPARTMENT
HT508V-5.08-XXP-1Y-00A(H)	DESSON

  

SCALE	SCALE
1:1	1:1