

ORTAC PLASTIC CABLE GLANDS SERIES



POLYAMIDE CABLE GLANDS FLAT TYPE CLOSED SEAL


TECHNICAL DETAILS

Material

Cap nut	: Polyamide PA6 V2 + 30% GF
Sealing ring	: TPV (special seal for dust resistance)
Washer	: Polystyrene
Gland body	: Polyamide PA6 V2
Connection thread	: Metric (EN 60423)/PG (DIN 40430)
Protection class	: IP54
Temperature range	: -20 °C + 100 °C

Properties

Dust resistance with special seal
UV resistance
DIN type design and clamping
Easy to assemble



DÜZ TİP RAKOR KAPALI CANTALI

Hammaddesi	: Polyamid PA6 V2
Renk	: RAL 7001 (Gri) : RAL 7035 (Açık Gri) : RAL 9005 (Siyah)
Bağlantı dişi M	: EN 60423
Bağlantı dişi PG	: DIN 40430
Koruma sınıfı	: IP54
Sürekli ısıya direnci	: -20 °C + 100 °C
Conta	: Termoplastik vulkanize TPV



RAL 7001



RAL 7035



RAL 9005

METRIC/PG THREAD CABLE GLANDS

AG Thread	Gray Code ■ RAL 7001	L. Gray Code ■ RAL 7035	Black Code ■ RAL 9005	H mm	GL mm	mm	mm	IP 54 Halogeen free
M 12 x 1,5	KMRG 17	KMRL 17	KMRB 17	21	8	15	3,5 - 6	
M 16 x 1,5	KMRG 18	KMRL 18	KMRB 18	22	8	19	4,5 - 7	
M 16 x 1,5	KMRG 19	KMRL 19	KMRB 19	22	8	22	6 - 9	
M 20 x 1,5	KMRG 20	KMRL 20	KMRB 20	26	9	24	9 - 12	
M 20 x 1,5	KMRG 21	KMRL 21	KMRB 21	28	10	27	11 - 14	
M 25 x 1,5	KMRG 22	KMRL 22	KMRB 22	32	11	33	14 - 18	
PG 7	KRG 11	KRL 11	KRB 11	21	8	15	3,5 - 6	
PG 9	KRG 12	KRL 12	KRB 12	22	8	19	4,5 - 7	
PG 11	KRG 13	KRL 13	KRB 13	22	8	22	6 - 9	
PG 13,5	KRG 14	KRL 14	KRB 14	26	9	24	9 - 12	
PG 16	KRG 15	KRL 15	KRB 15	28	10	27	11 - 14	
PG 21	KRG 16	KRL 16	KRB 16	32	11	33	14 - 18	
PG 29	KRG 17	KRL 17	KRB 17	35	11	42	18 - 25	
PG 36	KRG 18	KRL 18	KRB 18	39	13	53	25 - 32	