

ORTAC PLASTIC CABLE GLANDS SERIES



POLYAMIDE CABLE GLANDS DIN TYPE


TECHNICAL DETAILS

Material

Cap nut	: Polyamide PA6 V2 + 30% GF
Sealing ring	: TPV
Washer	: Polystyrene
Gland body	: Polyamide PA6 V2
Connection thread	: Metric (EN 60423)/PG (DIN 40430)
Protection class	: IP54
Temperature range	: -20 °C + 100 °C

Properties

UV resistance
DIN type design and clamping
Easy to assemble



DÜZ TİP RAKOR

Hammaddesi	: Polyamid PA6 V2
Renk	: RAL 7001 (Gri) : RAL 7035 (Açık Gri) : RAL 9005 (Siyah)
Bağlantı dişi M	: EN 60423
Bağlantı dişi PG	: DIN 40430
Koruma sınıfı	: IP54
Sürekli ısıya direnci	: -20 °C + 100 °C
Conta	: Termoplastik vulkanize TPV



■ RAL 7001



■ RAL 7035



■ RAL 9005

METRIC/PG THREAD CABLE GLANDS

PRODUCT RANGE OVERVIEW

AG Thread	Gray Code ■ RAL 7001	L. Gray Code ■ RAL 7035	Black Code ■ RAL 9005	H mm	GL mm	mm	mm	IP 54 Halogen free
M 12 x 1,5	DMRG 01	DMRL 01	DMRB 01	21	8	15	3,5 - 6	
M 16 x 1,5	DMRG 02	DMRL 02	DMRB 02	22	8	19	4,5 - 7	
M 16 x 1,5	DMRG 03	DMRL 03	DMRB 03	22	8	22	6 - 9	
M 20 x 1,5	DMRG 04	DMRL 04	DMRB 04	26	9	24	8 - 13	
M 20 x 1,5	DMRG 05	DMRL 05	DMRB 05	28	10	27	11 - 14	
M 25 x 1,5	DMRG 06	DMRL 06	DMRB 06	32	11	33	14 - 18	
PG 7	ORG 11	ORL 11	ORB 11	21	8	15	3,5 - 6	
PG 9	ORG 12	ORL 12	ORB 12	22	8	19	4,5 - 7	
PG 11	ORG 13	ORL 13	ORB 13	22	8	22	6 - 9	
PG 13,5	ORG 14	ORL 14	ORB 14	26	9	24	8 - 13	
PG 16	ORG 15	ORL 15	ORB 15	28	10	27	11 - 14	
PG 21	ORG 16	ORL 16	ORB 16	32	11	33	14 - 18	
PG 29	ORG 17	ORL 17	ORB 17	35	11	42	18 - 25	
PG 36	ORG 18	ORL 18	ORB 18	39	13	53	25 - 32	