



参考标准/Standard: UL, IEC
额定电压/Rated voltage: 150V, 250V
额定电流/Rated current: 20A, 24A
接触电阻/Contact resistance: 20m Ω
绝缘电阻/Insulation resistance: 500M Ω /DC500V
使用线径/Wire range: 22~12AWG(Ul), 2.5mm²(IEC)
耐电压/With standing voltage: AC 2000V/1 Min

机械性能/Mechanical

最大扭矩/Torque(Max): 12Nm(10.8lb.in)
瞬时温度/MAX Soldering: +250 $^{\circ}$ C for 5 Sec
温度范围/Temp Range: -40 $^{\circ}$ C~+105 $^{\circ}$ C

尺寸/Dimensions

间距/Pitch: 11mm

极数/Poles: 3~4P

材质及电镀/Material: 塑料/Housing
PAG6
M4 Steel imitation gold plated
焊丝/Screws: Brass imitation gold plated
焊针/Pin header

	linear dimension(Tolerances Standard GB/T 14486-2008)										\equiv					
variable range	6 to	over 6 to	over 10 to	over 18 to	over 30 to	over 50 to	over 80 to	over 120 to	over 160 to	over 200 to	over 250 to	all	5 to	over 5 to	over 30 to	over 120 to
tolerance	± 0.1	± 0.14	± 0.19	± 0.25	± 0.32	± 0.43	± 0.57	± 0.72	± 0.88	± 1.05	± 1.25	0.5	0.025	0.06	0.12	0.4

单位/UNITS	mm	尺寸/SIZE	A4	比例/SCALE	2:1	名称/TITLE	第三视图/THIRD ANGLE PROJECTION
						慈溪市万捷电子有限公司 CIXI WANJIE ELECTRONIC CO., LTD	EM-1H-XXP-1YY-00B